查询TWH104-H供应商

***Customer:**

Pb Free

SPECIFICATION

ITEM	CHIP LED DEVICE
MODEL	TWH104-H#
REVISION DATE	Rev0.2(061026)

[Contents]

1. Features
2. Absolute maximum ratings
3. Electro-optical characteristics
4. Ranks.
5. Characteristic diagrams
6. Soldering profile
7. Outline dimension
8. Packing
9. Reel packing structure
10. Precaution for use
11. RoHS

Drawn by	Checked by	Approved by

SEOUL SEMICONDUCTOR CO,. LTD.
148-29 Kasan-Dong, Keumchun-Gu, Seoul, Korea
TEL: 82-2-3281-6269 FAX: 82-2-858-5537

1. Features

□ Package : 1.6 × 0.8 × 0.4 mm

□ Color coordinates: X = 0. 29 Y = 0.28 according to CIE 1931

□ Tape and reel packing

2. Absolute Maximum Ratings (Ta=25℃)

Parameter	Symbol	Value	Unit
Power Dissipation	P_d	70	㎽
Forward Current	I_F	20	㎃
Peak Forward Current	I_{FM} *1	60	㎃
Reverse Voltage	V_R	5	V
Operating Temperature	T_{opr}	-30 ~ 80	℃
Storage Temperature	T_{stg}	-40 ~ 100	℃

*1 I_{FM} conditions: Pulse width Tw≤ 0.1ms, Duty ratio≤ 1/10

3. Electro-Optical Characteristics (Ta=25℃)

Characteristics	Symbol	Condition	Min	Typ	Max	Unit
Forward Voltage	V_F	I_F=5㎃	2.7	2.9	3.1	V
Zener Forward Voltage	$V_{F(Z)}$	I_F=10㎃	0.6	0.8	1.5	V
Luminous Intensity *2	I_V	I_F=5㎃	100	150	220	mcd
Chromaticity Coordinates *3	X	I_F=5㎃	0.230	0.275	0.321	
	Y	I_F=5㎃	0.220	0.265	0.310	
Viewing angle*3	$\Delta 1/2\theta$	I_F=5㎃	-	160	-	°

*2 The luminous intensity I_V is measured at the peak of the spatial pattern which may not be aligned with the mechanical axis of the LED package.

*3 The CIE standard colorimetric system

[Note] (Tolerance : I_V±10%, color coordinate ±0.01, V_F ±0.1)

SEOUL SEMICONDUCTOR CO,. LTD.
148-29 Kasan-Dong, Keumchun-Gu, Seoul, Korea
TEL: 82-2-3281-6269 FAX: 82-2-858-5537

4. Ranks

(1) Luminous Intensity: Iv [mcd]

Rank	Iv [mcd]	Condition
C	100~150	IF =5mA
D	150~220	

(2) Color Coordinate: x, y

Rank	A				Condition
x	0.230	0.270	0.285	0.245	I_F=5mA
y	0.220	0.220	0.250	0.250	

Rank	B				Condition
x	0.245	0.285	0.303	0.263	I_F=5mA
y	0.250	0.250	0.280	0.280	

Rank	C				Condition
x	0.263	0.303	0.281	0.321	I_F=5mA
y	0.280	0.280	0.310	0.310	

Rank	D				Condition
x	0.281	0.321	0.340	0.300	I_F=5mA
y	0.310	0.310	0.340	0.340	

(3) Forward voltage: V_F

Rank	V_F (V)		Condition
A	2.7	2.8	IF = 5mA
B	2.8	2.9	
C	2.9	3.0	
D	3.0	3.1	

SEOUL SEMICONDUCTOR CO,. LTD.
148-29 Kasan-Dong, Keumchun-Gu, Seoul, Korea
TEL: 82-2-3281-6269 FAX: 82-2-858-5537

5. Characteristic Diagram

Forward Current vs. Forward Voltage



Luminous Intensity vs. Forward Current



Forward Current Derating Curve



Forward Current vs Chromaticity Coordinate



SEOUL SEMICONDUCTOR CO,. LTD.
148-29 Kasan-Dong, Keumchun-Gu, Seoul, Korea
TEL: 82-2-3281-6269 FAX: 82-2-858-5537

Radiation Diagram



Spectrum



SEOUL SEMICONDUCTOR CO,. LTD.
148-29 Kasan-Dong, Keumchun-Gu, Seoul, Korea
TEL: 82-2-3281-6269 FAX: 82-2-858-5537

6. Soldering Profile

Reflow Soldering Conditions/ Profile

(1) Lead Solder

-Preliminary heating to be at 150℃max. for 2 minutes max.

-Soldering heat to be at 240℃max. for 5 seconds max.



(2) Lead-Free Solder

-Preliminary heating to be at 150℃max. for 2 minutes max.

-Soldering heat to be at 260℃max. for 10 seconds max.



(3) Hand Soldering conditions

-Not more than 3 seconds @MAX280℃, under Soldering iron.

SEOUL SEMICONDUCTOR CO,. LTD.
148-29 Kasan-Dong, Keumchun-Gu, Seoul, Korea
TEL: 82-2-3281-6269 FAX: 82-2-858-5537

7. Outline Dimension

Tolerance: ±0.1, Unit: ㎜



[Recommended Solder Pattern]

8. Packing





Tolerance ±0.2, Unit : mm

(1) Quantity : 4000pcs/Reel

(2) Cumulative Tolerance : Cumulative Tolerance/10 pitches to be ±0.2mm

(3) Adhesion Strength of Cover Tape : Adhesion strength to be 0.1-0.7N when the cover tape is turned off from the carrier tape at 10℃ angle to be the carrier tape

(4) Package : P/N, Manufacturing data Code No. and quantity to be indicated on a damp proof Package.

SEOUL SEMICONDUCTOR CO,. LTD.
148-29 Kasan-Dong, Keumchun-Gu, Seoul, Korea
TEL: 82-2-3281-6269 FAX: 82-2-858-5537

9. Reel Packing Structure

Reel



Aluminum Vinyl Bag



Outer Box

*Material: Paper(SW3B(B))

TYPE	SIZE(mm)		
	ⓐ	ⓑ	ⓒ
7inch	245	220	142



SEOUL SEMICONDUCTOR CO,. LTD.
148-29 Kasan-Dong, Keumchun-Gu, Seoul, Korea
TEL: 82-2-3281-6269 FAX: 82-2-858-5537

10. **Precaution for use**

(1) Storage

In order to avoid the absorption of moisture, it is recommended to store in the dry box (or desiccator) with a desiccant . Otherwise, to store them in the following environment is recommended.

Temperature : 5℃~30℃ Humidity : 60%HR max.

(2) Attention after opened

However LED is correspond SMD, when LED be soldered dip, interfacial separation may affect the light transmission efficiency, causing the light intensity to drop. Attention in followed.

a. After opened and mounted, the soldering shall be quickly.

b. Keeping of a fraction

Temperature : 5 ~ 40℃ Humidity : less than 30%

(3) In case of more than 1 week passed after opening or change color of indicator on desiccant components shall be dried 10-12hr. at 60±5℃.

(4) In case of supposed the components is humid, shall be dried dip-solder just before.

100Hr at 80±5℃ or 12Hr at 100±5℃.

(5) Any mechanical force or any excess vibration shall not be accepted to apply during cooling process to normal temp. after soldering.

(6) Quick cooling shall not be avoid.

(7) Components shall not be mounted on warped direction of PCB.

(8) Anti radioactive ray design is not considered for the products listed here in.

(9) This device should not be used in any type of fluid such as water, oil, organic solvent and etc. When washing is required, IPA should be used.

(10) When the LEDs are illuminating, operating current should be decided after considering the ambient maximum temperature.

(11) LEDs must be stored to maintain a clean atmosphere. If the LEDs are stored for 3 months or more after being shipped from SSC, a sealed container with a nitrogen atmosphere should be used for storage.

(12) The LEDs must be soldered within seven days after opening the moisture-proof packing.

(13) Repack unused products with anti-moisture packing, fold to close any opening and then store in a dry place.

(14) The appearance and specifications of the product may be modified for improvement without notice.

10. RoHS

Korea Environment &
Merchandise Testing Institute
459-28 GASAN-DONG, GEUMCHEON-GU, SEOUL, KOREA
TEL : 82-2-2102-2500 FAX : 82-2-856-5618 http://www.kemti.org

TEST REPORT

No. : 18570 Date Out : JUN. 28, 2005
Client : SEOUL SEMICONDUCTOR CO., LTD. Date In : JUN. 21, 2005
Address : #148-29, Gasan-dong, Geumcheon-gu, Seoul, Korea Test Date : JUN. 28, 2005
Buyer : LS INDUSTRIAL SYSTEM CO., LTD.
Sample Description : TWH104-H
Test Results : Refer to the next page

Signed by

Kyung Hwan Yu, Manager
Env. Testing Department

Our report apply only to the standards or procedures identified and to the sample(s) tested unless otherwise specified. The test results are not indicative of representative of the qualities of the lot from which the sample was taken or of apparently identical or similar products.

- Page 1of 2-

KEMTI 459-28 GASAN-DONG, GEUMCHEON-GU, SEOUL, KOREA TEL:82-2-2102-2500, FAX:82-2-856-5618 http://www.kemti.org

No. : 18570 [TEST RESULT]

Items	Unit	Test Results	Test Methods
Lead(Pb)	mg/kg	Not detected (Detection limit 2)	USEPA 3051 Analytical instrument : ICP-AES
Cadmium(Cd)	mg/kg	Not detected (Detection limit 1)	USEPA 3051 Analytical instrument : ICP-AES
Mercury(Hg)	mg/kg	Not detected (Detection limit 1)	USEPA 3051 Analytical instrument : ICP-AES
Chromium VI(Cr^{6+})	μg/EA	Not detected (Detection limit 0.1)	ISO 3613:2000(E) UV-Vis. Spectrophotometer
Polybrominated Biphenyls(PBBs)			
Bromobiphenyl	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Dibromobiphenyl	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Tribromobiphenyl	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Tetrabromobiphenyl	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Pentabromobiphenyl	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Hexabromobiphenyl	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Heptabromobiphenyl	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Octabromobiphenyl	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Decabromobiphenyl	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Polybrominated Diphenyl Ethers(PBDEs)			
Bromodiphenyl ether	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Dibromodiphenyl ether	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Tribromodiphenyl ether	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Tetrabromodiphenyl ether	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Pentabromodiphenyl ether	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Hexabromodiphenyl ether	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Heptabromodiphenyl ether	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Octabromodiphenyl ether	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Nonabromodiphenyl ether	mg/kg	Not detected (Detection limit 1)	GC-MS analysis
Decabromodiphenyl ether	mg/kg	Not detected (Detection limit 1)	GC-MS analysis

SEOUL SEMICONDUCTOR CO,. LTD.
148-29 Kasan-Dong, Keumchun-Gu, Seoul, Korea
TEL: 82-2-3281-6269 FAX: 82-2-858-5537

♦ Rank Division

Iv [mcd] (I_F=5 mA)	Color coordinate (I_F=5 mA)	VF [V] (I_F=5 mA)	**Rank**	Product
C	A	A	**CAA**	
C	A	B	**CAB**	
C	A	C	**CAC**	
C	A	D	**CAD**	
D	A	A	**DAA**	
D	A	B	**DAB**	
D	A	C	**DAC**	
D	A	D	**DAD**	
C	B	A	**CBA**	
C	B	B	**CBB**	
C	B	C	**CBC**	
C	B	D	**CBD**	
D	B	A	**DBA**	
D	B	B	**DBB**	
D	B	C	**DBC**	
D	B	D	**DBD**	
C	C	A	**CCA**	
C	C	B	**CCB**	
C	C	C	**CCC**	
C	C	D	**CCD**	
D	C	A	**DCA**	
D	C	B	**DCB**	
D	C	C	**DCC**	
D	C	D	**DCD**	
C	D	A	**CDA**	
C	D	B	**CDB**	
C	D	C	**CDC**	
C	D	D	**CDD**	
D	D	A	**DDA**	
D	D	B	**DDB**	
D	D	C	**DDC**	
D	D	D	**DDD**	

SSC-TWH104-HS

SSC-TWH104-HL